

## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

## Detaseal® hydroflow soft 2 putty (base + catalyst)

Revision date: 10.08.2018 Product code: 11092 Page 1 of 8

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Detaseal® hydroflow soft 2 putty (base + catalyst)

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Impression material for use in dental technology.

## 1.3. Details of the supplier of the safety data sheet

Company name: DETAX GmbH & Co. KG
Street: Carl-Zeiss-Strasse
Place: D-76275 Ettlingen

Telephone: +49 7243/510-0 Telefax: +49 7243/510-100

e-mail: post@detax.de
Internet: www.detax.de
Responsible Department: Emergency number: +49 7243/510-0

This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 a.m. - 4.00 p.m.)

**1.4. Emergency telephone** +49 7243/510-0

number: This number is only obtainable during office hours (Monday - Thursday 8.00 a.m.

- 5.00 p.m., Friday 8.00 - 4.00 p.m.)

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

This mixture is not classified as hazardous in accordance with Regulation (EC) No. 1272/2008.

### 2.2. Label elements

# Regulation (EC) No. 1272/2008

### Special labelling of certain mixtures

EUH210 Safety data sheet available on request.

### Additional advice on labelling

According to Regulation (EC) 1272/2008, art.1 No. 5 (d) this product as a medical product must not be labelled!

### 2.3. Other hazards

No information available.

# **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

## **Chemical characterization**

Contains polydimethylsiloxane with functional groups. + fillers and pigment catalyst: additionally platinum complex compound.



according to Regulation (EC) No 1907/2006

# Detaseal® hydroflow soft 2 putty (base + catalyst)

Revision date: 10.08.2018 Product code: 11092 Page 2 of 8

### **Hazardous components**

CAS No	Chemical name			
	EC No	Index No	REACH No	
	Classification according to Regula			
14464-46-1	cristobalite flour	20 - < 25 %		
	238-455-4			
	STOT RE 1; H372			
8042-47-5	paraffin oil	5 - < 10 %		
	232-455-8		01-2119487078-27	
	Asp. Tox. 1; H304			
556-67-2	octamethylcyclotetrasiloxane		< 0,5 %	
	209-136-7	014-018-00-1	01-2119529238-36	
	Flam. Liq. 3, Repr. 2, Aquatic Chro			
540-97-6	Dodecaemthylcyclohexasiloxane	< 0,5 %		
	208-762-8		01-2119517435-42	
541-02-6	Decamethylcyclopentasiloxane	< 0,5 %		
	208-764-9		01-2119511367-43	

Full text of H and EUH statements: see section 16.

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

## General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

## After inhalation

Provide fresh air.

## After contact with skin

Remove product mechanically with cloth or paper. Wash with plenty of water and soap. In case of visible changes on the skin or complaints, seek medical advice (if possible have label or safety data sheet with you).

#### After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

## After ingestion

Rinse mouth immediately and drink plenty of water. Let water be drunken in little sips (dilution effect).

Do not induce vomiting. If you feel unwell, seek medical advice.

## 4.2. Most important symptoms and effects, both acute and delayed

No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings.

### 5.2. Special hazards arising from the substance or mixture

Non-flammable. Vapours can form explosive mixtures with air.





according to Regulation (EC) No 1907/2006

## Detaseal® hydroflow soft 2 putty (base + catalyst)

Revision date: 10.08.2018 Product code: 11092 Page 3 of 8

#### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protection equipment.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains.

## 6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

### 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

No special measures are necessary.

### Advice on protection against fire and explosion

No special fire protection measures are necessary.

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed.

#### Advice on storage compatibility

Do not store with acids, lyes, alcohols, metallic powders and metallic oxides (release of hydrogen is favoured).

### Further information on storage conditions

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs.

### 7.3. Specific end use(s)

Silicone material for the fabrication of gingival epithesis./ Impression material oral For use by trained specialist staff.

### **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

# 8.2. Exposure controls

#### Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

### Eye/face protection

Wear eye/face protection.

#### Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Detaseal® hydroflow soft 2 putty (base + catalyst)

Revision date: 10.08.2018 Product code: 11092 Page 4 of 8

supplier of these gloves.

Suitable are gloves of the following material: NBR (Nitrile rubber)

Skin protection

Wear suitable protective clothing.

**Respiratory protection** 

In case of inadequate ventilation wear respiratory protection.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Paste

Colour: base: yellow, catalyst: white

Odour: like mango

Test method

pH-Value: not determined

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

not determined
not determined

Flash point: >100 °C DIN 51755

**Flammability** 

Solid: not applicable
Gas: not applicable
Lower explosion limits: not determined
Upper explosion limits: not determined

Ignition temperature: >400 °C DIN 51794

**Auto-ignition temperature** 

Solid: not applicable
Gas: not applicable
Decomposition temperature: >180 °C

**Oxidizing properties** 

Not oxidizing.

Vapour pressure: <10 hPa

(at 20 °C)

Density (at 20 °C): 1,30 g/cm³ DIN 51757

Water solubility: insoluble

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: 5000000 mPa·s BROOKFIELD

(at 23 °C)

Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined

## **SECTION 10: Stability and reactivity**



according to Regulation (EC) No 1907/2006

# Detaseal® hydroflow soft 2 putty (base + catalyst)

Revision date: 10.08.2018 Product code: 11092 Page 5 of 8

#### 10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

### 10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

# 10.3. Possibility of hazardous reactions

Reacts with : Acids, alkalis, alcohols, powdered metals or metal oxides with release of hydrogen.

#### 10.4. Conditions to avoid

Temperatures > 150°C/ 302 °F.

### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

In case of thermic decomposition hydrogen is released.

At a temperature of approx. 150°C/ 302°F a small amount of formaldehyde can be released by oxidative degradation.

# **SECTION 11: Toxicological information**

## 11.1. Information on toxicological effects

### **Acute toxicity**

Based on available data, the classification criteria are not met.

For the product itself no toxicological data are available. In products with a comparable composition, a LD50 (orally, species rat) of > 5000 mg/kg has been found.

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
8042-47-5	paraffin oil						
	oral	LD50 mg/kg	>5000	Rat	OECD		
	dermal	LD50 mg/kg	>2000	Rabbit	OECD		
556-67-2	octamethylcyclotetrasiloxane						
	oral	LD50 mg/kg	4800	Rat		OECD 401	
	dermal	LD50 mg/kg	>2400	Rabbit		OECD 402	
	inhalation (4 h) vapour	LC50	36 mg/l	Rat	GESTIS	OECD 403	
540-97-6	Dodecaemthylcyclohexasiloxane						
	oral	LD50 mg/kg	2000	Rat			
	dermal	LD50 mg/kg	2000	Rat			
541-02-6	Decamethylcyclopentasiloxane						
	oral	LD50 mg/kg	>24100	Rat	GESTIS		
	dermal	LD50 mg/kg	>2000	Rabbit		OECD 402	
	inhalation (4 h) vapour	LC50	8,67 mg/l	Rat		OECD 403	

#### Irritation and corrosivity

Based on available data, the classification criteria are not met.



according to Regulation (EC) No 1907/2006

# Detaseal® hydroflow soft 2 putty (base + catalyst)

Revision date: 10.08.2018 Product code: 11092 Page 6 of 8

#### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

Due to physical form (paste) classification with H372 is not appropriate. An inhalation of the product is not possible.

EC regulation 1272/2008 annex 1, section 1.1.1.5: "For the purpose of classification of health hazards (part 3), the route of exposure, information on mechanisms and metabolism studies are useful for determining the relevance of effects in humans. If this information raises doubts as to their relevance in humans, in spite of the indisputable data legitimacy and quality, a lower classification may be justified. When there is scientific evidence that the mechanism or mode of action is not relevant to humans, the substance or mixture should not be classified."

#### **Aspiration hazard**

Based on available data, the classification criteria are not met.

### Additional information on tests

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP].

## **SECTION 12: Ecological information**

#### **12.1. Toxicity**

The product is not: Ecotoxic.

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h]   [d] Species	Source	Method		
8042-47-5	paraffin oil						
	Acute fish toxicity	LC50 >1000 mg/l	96 h Leuciscus idus (golden orfe)	OECD			

### 12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
556-67-2	octamethylcyclotetrasiloxane					
		3,7%	29			
	Not readily biodegradable (according to OECD criteria)	-				

# 12.3. Bioaccumulative potential

The product has not been tested.

#### 12.4. Mobility in soil

The product has not been tested.

### 12.5. Results of PBT and vPvB assessment

Dodecamethylcyclohexasiloxane (D6) fulfills the current criteria set forth under Annex XIII of the EU REACH Regulation for very persistent and very bioaccumulative substances (vPvB) and was included in the candidate list of substances of very high concern (SVHC). According to our knowledge of the state of the art, however, D6 cannot be compared with known persistent, bioaccumulative and toxic (PBT) and/or vPvB substances. The interpretation of the available data by the silicone industry reveals that scientific evidence obtained from field tests essentially points out that D6 does not lead to biomagnification in aquatic and terrestrial food chains. In air, D6 is decomposed by naturally occurring processes in the atmosphere. D-residues which do not



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Detaseal® hydroflow soft 2 putty (base + catalyst)

Revision date: 10.08.2018 Product code: 11092 Page 7 of 8

decompose in this way in the air are not expected to accumulate from the air in water, the soil or living organisms.

Decamethylcyclopentasiloxane (D5) fulfills the current criteria set forth under Annex XIII of the EU REACH Regulation for vPvB substances and was included in the candidate list of SVHCs. According to our knowledge of the state of the art, however, D5 cannot be compared with known PBT and/or vPvB substances. The interpretation of the available data by the silicone industry reveals that scientific evidence obtained from field tests essentially points out that D5 does not lead to biomagnification in aquatic and terrestrial food chains. In air, D5 is decomposed by naturally occurring processes in the atmosphere. D-residues which do not decompose in this way in the air are not expected to accumulate from the air in water, the soil or living organisms.

Octamethylcyclotetrasiloxane (D4) fulfills the current criteria set forth under Annex XIII of the EU REACH Regulation for PBT and vPvB substances and was included in the candidate list of SVHCs. According to our knowledge of the state of the art, however, D4 cannot be compared with known PBT and/or vPvB substances. The interpretation of the available data by the silicone industry reveals that scientific evidence obtained from field tests essentially points out that D4 does not lead to biomagnification in aquatic and terrestrial food chains. In air, D4 is decomposed by naturally occurring processes in the atmosphere. D-residues which do not decompose in this way in the air are not expected to accumulate from the air in water, the soil or living organisms.

### 12.6. Other adverse effects

No information available.

#### **Further information**

Avoid release to the environment.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

#### Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

#### Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

# Inland waterways transport (ADN)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

# Marine transport (IMDG)

14.1. UN number:No dangerous good in sense of this transport regulation.14.2. UN proper shipping name:No dangerous good in sense of this transport regulation.14.3. Transport hazard class(es):No dangerous good in sense of this transport regulation.14.4. Packing group:No dangerous good in sense of this transport regulation.

# Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** No dangerous good in sense of this transport regulation.



# **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

# Detaseal® hydroflow soft 2 putty (base + catalyst)

Revision date: 10.08.2018 Product code: 11092 Page 8 of 8

No dangerous good in sense of this transport regulation. 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): 14.4. Packing group: No dangerous good in sense of this transport regulation.

### 14.6. Special precautions for user

No dangerous good in sense of this transport regulation.

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No dangerous good in sense of this transport regulation.

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

### **Additional information**

The mixture contains substances of very high concern (SVHC candidates):

Dodecamethylcyclohexasiloxane (D6), CAS no. 540-97-6 Decamethylcyclopentasiloxane (D5), CAS no. 541-02-6 Octamethylcyclotetrasiloxane (D4), CAS no. 556-67-2

### **National regulatory information**

Water contaminating class (D): 1 - slightly water contaminating

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

## Relevant H and EUH statements (number and full text)

Flammable liquid and vapour. H226 H361f Suspected of damaging fertility.

May cause long lasting harmful effects to aquatic life. H413

**EUH210** Safety data sheet available on request.

### **Further Information**

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singulary responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)