

Safety Data Sheet

according to Regulation (EC) No 1907/2006

sili spray Adhesive

Revision date: 20.11.2018

Product code: 10109

Page 2 of 10

Pictograms:



Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Additional advice on labelling

According to Regulation (EC) 1272/2008, art.1 No. 5 (d) this product as a medical product must not be labelled!

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Organic solvent in propellant (liquefied butane gas)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

sili spray Adhesive

Revision date: 20.11.2018

Product code: 10109

Page 3 of 10

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha			15 - < 20 %
	265-151-9	649-328-00-1		
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
141-78-6	ethyl acetate			15 - < 20 %
	205-500-4	607-022-00-5	02-2119752482-38	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
79-20-9	methyl acetate			1 - < 5 %
	201-185-2	607-021-00-X	02-2119752526-34	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
110-54-3	n-hexane			< 1 %
	203-777-6	601-037-00-0		
	Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1, Aquatic Chronic 2; H225 H361f H315 H336 H373 H304 H411			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water. Do not induce vomiting. If you feel unwell, seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

according to Regulation (EC) No 1907/2006

sili spray Adhesive

Revision date: 20.11.2018

Product code: 10109

Page 4 of 10

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: @0102.B010927. Pyrophoric or self-heating substances. Do not store with flammable liquids, flammable solid substances or desensitised substances, spontaneously flammable substances, substances liberating flammable gases in contact with water, combustible liquids.

Further information on storage conditions

Keep only in the original container in a cool, dry and well-ventilated place, away from foodstuffs.

7.3. Specific end use(s)

Aerosol for better adhesion of condensation curing dental impression materials on impression trays.

For use by trained specialist staff.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

sili spray Adhesive

Revision date: 20.11.2018

Product code: 10109

Page 5 of 10

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
79-20-9	Methyl acetate	200	616		TWA (8 h)	WEL
		250	770		STEL (15 min)	WEL
110-54-3	n-Hexane	20	72		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Suitable are gloves of the following material: Butyl caoutchouc (butyl rubber), FKM (fluoro rubber)

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquefied gas with liquid and solid parts, compressed
 Colour: blue
 Odour: faintly like esters

Test method

pH-Value: not determined

Changes in the physical state

Melting point: not determined
 Initial boiling point and boiling range: not determined

Flash point: <-10 °C DIN 51755

Flammability

Solid: not applicable

according to Regulation (EC) No 1907/2006

sili spray Adhesive

Revision date: 20.11.2018

Product code: 10109

Page 6 of 10

Gas:	not applicable
Lower explosion limits:	1,5 vol. %
Upper explosion limits:	8,5 vol. %
Ignition temperature:	365 °C DIN 51794
Auto-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined
Oxidizing properties	
Not oxidizing.	
Vapour pressure: (at 70 °C)	9000 hPa
Density (at 15 °C):	0,74 g/cm ³ DIN 51757
Water solubility:	insoluble
Solubility in other solvents	
not determined	
Partition coefficient:	not determined
Vapour density:	not determined
Evaporation rate:	not determined
9.2. Other information	
Solid content:	not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Reacts with : flammable, spontaneously flammable and combustible substances. Prevent any contact of the product with strong oxidising agents, such as chlorine or concentrated oxygen.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Higher temperatures advance the formulation of explosive vapour-air mixtures, therefore don't expose the product to increased temperatures.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

The following applies for the silicone content of the product: At temperature of appr. 150°C/ 302 °F a small amount of formaldehyde can be released by oxidative degradation.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

sili spray Adhesive

Revision date: 20.11.2018

Product code: 10109

Page 7 of 10

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha				
	oral	LD50 mg/kg	2000	Rat	
	dermal	LD50 mg/kg	4000	Rabbit	
	inhalation (4 h) vapour	LC50	54 mg/l	Rat	
141-78-6	ethyl acetate				
	oral	LD50 mg/kg	5620	Rat	GESTIS
	dermal	LD50 mg/kg	>18000	Rabbit	GESTIS
79-20-9	methyl acetate				
	oral	LD50 mg/kg	>5000	Rat	GESTIS
	dermal	LD50 mg/kg	>5000	Rabbit	GESTIS
	inhalation (4 h) vapour	LC50	49-98 mg/l	Rat	
110-54-3	n-hexane				
	oral	LD50 mg/kg	25000	Rat	GESTIS
	inhalation (4 h) vapour	LC50	169 mg/l	Rat	GESTIS

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha; ethyl acetate)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

sili spray Adhesive

Revision date: 20.11.2018

Product code: 10109

Page 8 of 10

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
141-78-6	ethyl acetate					
	Acute fish toxicity	LC50	328 mg/l	96 h	Pimephales promelas (fathead minnow)	GESTIS
	Acute algae toxicity	ErC50 mg/l	2500	96 h		GESTIS
	Acute crustacea toxicity	EC50	679 mg/l	48 h	Daphnia magna (Big water flea)	GESTIS
79-20-9	methyl acetate					
	Acute fish toxicity	LC50	320 mg/l	96 h	Pimephales promelas (fathead minnow)	
	Acute algae toxicity	ErC50 mg/l	>120	72 h	Desmodesmus subspicatus.	OECD 201
	Acute crustacea toxicity	EC50 mg/l	1027	48 h	Daphnia magna (Big water flea)	OECD 202
110-54-3	n-hexane					
	Acute fish toxicity	LC50 mg/l	57,8	96 h	Pimephales promelas	GESTIS

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
141-78-6	ethyl acetate				
	OECD 301D/ EEC 92/69/V, C.4-E	>70%	28		

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
110-54-3	n-hexane	3,9

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

Not identified as PBT/ vPvB substances

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the

according to Regulation (EC) No 1907/2006

sili spray Adhesive

Revision date: 20.11.2018

Product code: 10109

Page 9 of 10

substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Limited quantity:	1 L/ 30 kg
Transport category:	2
Tunnel restriction code:	D

Other applicable information (land transport)

Flammable gas

Marine transport (IMDG)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Marine pollutant:	-
Limited quantity:	1000 mL/ 30 kg
EmS:	F-D, S-U

Other applicable information (marine transport)

Flash point: <-10°C c.c.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS, flammable
14.3. Transport hazard class(es):	2.1
14.4. Packing group:	-
Hazard label:	2.1
Limited quantity Passenger:	30 kg G
Passenger LQ:	Y203
Excepted quantity:	E0
IATA-packing instructions - Passenger:	203
IATA-max. quantity - Passenger:	75 kg
IATA-packing instructions - Cargo:	203
IATA-max. quantity - Cargo:	150 kg

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

sili spray Adhesive

Revision date: 20.11.2018

Product code: 10109

Page 10 of 10

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; butane

Additional information

Aerosol directive (75/324/EEC).

National regulatory information

Employment restrictions:

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D):

2 - clearly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service
 LC50: Lethal concentration, 50%
 LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
Skin Irrit. 2; H315	Bridging principle "Aerosols"
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H222 Extremely flammable aerosol.
 H225 Highly flammable liquid and vapour.
 H229 Pressurised container: May burst if heated.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)